

SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF

Specifically formulated with a combination of synthetic base stock and advanced additive technology to meet and exceed the wear and frictional requirements of most automatic transmissions regardless of age. Recommended for a wide range of vehicles requiring Dexron-VI, Ford Mercon LV and 6+ speed automatic transmissions.

TYPICAL PROPERTIES	SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF
SPECIFIC GRAVITY @ 15°C	0.868
KINEMATIC VISCOSITY CST @ 40°C	28.7
KINEMATIC VISCOSITY CST @ 100°C	5.9
VISCOSITY INDEX (D2270)	154
BROOKFIELD VISCOSITY @ -40°C	102000
FLASH POINT (D92), °C	208
POUR POINT (D97), °C	-51
COLOUR	RED

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

RECOMMENDED FOR ALL AUTOMATIC TRANSMISSIONS, POWER SHIFTS AND HYDRAULIC SYSTEMS FOR:

- GM DEXRON®-VI LICENSED;
- FORD MERCON® LV

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF

APPLICATIONS

RECOMMENDED FOR ALL AUTOMATIC TRANSMISSIONS, POWER SHIFTS AND HYDRAULIC SYSTEMS FOR:

- (FF-WSS-M2C-938A/SF, XT-10 QLV) LICENSED;
- AISIN WARNER JWS 3309 (T-IV) & JWS 3324 (WS);
- AMERICAN MOTORS ATF +3 (MS7176-E), ATF +4 (MS9602);
- AUDI 5 HP LT71141 (ZF 5 HP18FL/19FL/24A);
- AUDI G 055 025 A2 (JWS 3309) ;
- BMW LT71141(ZF 5 HP18FL/19FL/24A);
- BMW 7045E;
- BMW MINI;
- CHRYSLER ATF+, +2, +3 (MS 7176E), +4 (MS 9602) CHRYSLER/DODGE MOPAR AS 68 RC (T-IV) JWS 3309, CHRYSLER AS68 RC – T IV;
- DAIHATSU AMMIX ATF D-II;
- ESSO LT 71141;
- FORD MERCON® FORD FNR5
- FORD M2C166H;
- FORD WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309;
- ACURA ATF-Z1;
- ALLISON C-3 & C-4;
- ATF RED 1, RED 1K;
- AUDI G 052 162-A1/A2
- BMW JWS 3309 (T-IV) BMW LA2634;
- BMW ZF 5HP18FL, 5HP24, 5HP30;
- BMW ETL-8072B;
- CAT TO-2;
- DAEWOO LT 71141;
- DAIHATSU AMMIX ATF D-III SP;
- FIAT T-IV TYPE, JWS 3309;
- FORD M2C138CJ;
- FORD WSS M2C 138CJ, 166H;
- FUSO ATF-II;

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF

APPLICATIONS

RECOMMENDED FOR ALL AUTOMATIC TRANSMISSIONS, POWER SHIFTS AND HYDRAULIC SYSTEMS FOR:

- FUSO ATF-SPIII;
- GM9986195 (AISIN AW, JWS 3309);
- GM DEXRON®-II;
- GM DEXRON®-IIE;
- GM DEXRON®-IIIH;
- HONDA ATF-Z1 (EXCEPT IN CVTS);
- HYUNDAI/KIA SP-IV;
- KIA SP-IV-RR; HYUNDAI/KIA SP-III;
- ISUZU BESCO ATF-II; ISUZU BESCO ATF III;
- JAGUAR ATF LT71141, ZF 5HP24;
- JAGUAR ATF 3403 JLM20238, JASO M315-2013 1A-LV;
- LEXUS JWS 3309;
- MAZDA ATF D-II;
- MAZDA ATF M-V;
- MAZDA ATF F-1;
- FUSO ATF-A4;
- GM TASA;
- GM DEXRON®-IID;
- GM DEXRON®-IIIG;
- HINO BLUE RIBBON ATF;
- HONDA DW-1;
- HYUNDAI/KIA SP-IV M; HYUNDAI/
- HYUNDAI/KIA DEX-II/ SP-II; HYUNDAI/KIA JWS 3314; HYUNDAI/KIA JWS 9683;
- JAGUAR ATF 3403 M115, ATF 3403-M115;
- JAGUAR JLM20238;
- JEEP ATF+3, +4;
- KIA ATF SP-II, SP-III, SP-IV, SP-IVM, RED 1;
- MAZDA ATF M-III;
- MAZDA ATF FZ;
- MAZDA ATF S-1;

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF

APPLICATIONS

RECOMMENDED FOR ALL AUTOMATIC TRANSMISSIONS, POWER SHIFTS AND HYDRAULIC SYSTEMS FOR:

- MAZDA ATF N-1;
- MB 236.1;
- 236.2;
- MB 236.5;
- MB 236.7;
- MB 236.9;
- MITSUBISHI DIAQUEEN AW; MITSUBISHI DIAQUEEN J2;
- NAG 1 (CHRYSLER, JEEP, CHEROKEE);
- NISSAN MATIC FLUID J; NISSAN MATIC FLUID K;
- PEUGEOT ZF 4HP20; PORSCHE ZF 5HP19FL, ZF 5HP20, LT71141;
- SAAB T-IV (JWS 3309); SAAB 93 165 147;
- SHELL 3403, M115, LA 2634; SUBARU ATF;
- SUBARU DEXRON®-II;
- SUZUKI AT OIL 5D06;
- MAZDA ATF 3317
- MB
- MB 236.3;
- MB 236.6;
- MB 236.8;
- MINI COOPER T-IV; MITSUBISHI DIAQUEEN SK; MITSUBISHI DIAQUEEN SP-II; MITSUBISHI DIAQUEEN SP-III; MITSUBISHI DIAQUEEN SP-IV;
- MITSUBISHI DIAQUEEN J3; MITSUBISHI DIAQUEEN ATF PA;
- NISSAN MATIC FLUID C; NISSAN MATIC FLUID D;
- NISSAN MATIC FLUID S; OPEL (ALL VEHICLES);
- PORSCHE ATF 3403-M115; PORSCHE T-IV (JWS 3309);
- SATURN T-IV (JWS 3309); SCION (ALL VEHICLES);
- SUBARU ATF 5AT;
- SUBARU ATF, ATF HP;
- SUZUKI ATF 2326;

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC MULTI VEHICLE LOW VISCOSITY ATF

APPLICATIONS

RECOMMENDED FOR ALL AUTOMATIC TRANSMISSIONS, POWER SHIFTS AND HYDRAULIC SYSTEMS FOR:

- SUZUKI ATF 2384K;
- SUZUKI ATF 3314;
- TEXACO 7045-E;
- TEXACO N402;
- TOYOTA ATF D-III;
- TOYOTA ATF T-IV;
- VICKERS M2950-S, I-286-S; ;
- VOLVO CE 97340;
- VW 5HP (18FL, 30);
- VW G-055-025 A2 (JWS 3309);
- ZF ALL 3 & 4 SPEED TRANSMISSION
- ZF TE-ML 09X;
- SUZUKI JWS 3309;
- SUZUKI ATF 3317;
- TEXACO 8072B;
- TOYOTA ATF D-II ;
- TOYOTA ATF T-III;
- TOYOTA ATF WS;
- VOITH 55.6335.XX (G607)
- VW 5 HP (ZF 5 HP 30);
- VW 5HP (19FL, 24A);
- VW TL 521 62;
- ZF TE-ML 09;
- ZF TE-ML 11;
- ZF 8HP;
- ZF 9HP

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

