

## AUTOMATIC TRANSMISSION FLUID (DEXRON III MERCON)

Formulated using highly refined, paraffinic base oils, additive systems and a shear stable VI enhanced thermal and oxidation stability, seal compatibility, friction control, rust, corrosion and wear protection. It helps prevent the accumulation and formation of sludge, varnish and foam deposits.

TYPICAL PROPERTIES	ATF
DENSITY KG/L @ 15°C	0.855
KINEMATIC VISCOSITY CST @ 40°C	37
KINEMATIC VISCOSITY CST @ 100°C	7.3
VISCOSITY INDEX (D2270)	173
BROOKFIELD VISCOSITY @ -40°C	17000
FLASH POINT (D92), °C	177
POUR POINT (D97), °C	-48
COLOUR	RED

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- ALLISON C-4 (APPROVAL # C4-25573197)
- FORD MERCON: M-980508

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*





## AUTOMATIC TRANSMISSION FLUID (DEXRON III MERCON)

### APPLICATIONS

### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- GM: DEXRON-III, DEXRON-II, DEXRON-G34447

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



**ILMA**  
Independent Lubricant Manufacturers Association