



DEF (DIESEL EXHAUST FLUID)

BOSS DEF ia a manufactured product of technically pure urea mixed with demineralised water designed to meet the specifications of DIN 70070:2005 and ISO 22241-1:2006 for NOx Abatement technologies. BOSS DEF is certified as a diesel exhaust fluid by the American Petroleum Institute (API).

UREA CONCENTRATION	32.5=/-0.7%
SPECIFIC GRAVITY @ 20°C (68°F)	1.087 - 1.093 KG/M3
REFRACTIVE INDEX @ 20°C	1.3814 - 1.3843
FREE AMMONIA (ALKALINITY)	0.2% MAX
BIURET	0.3% MAX
FORMALDEHYDE	NONE
INSOLUBLE MATTER	20 PPM MAX
PHOSPHATES	0.5 PPM MAX
CALCIUM	0.5 PPM MAX
IRON	0.5 PPM MAX
COPPER	0.2 PPM MAX
ZINC	0.2 PPM MAX
CHROMIUM	0.2 PPM MAX
NICKEL	0.2 PPM MAX

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





DEF (DIESEL EXHAUST FLUID)

ALUMINUM	0.5 PPM MAX
MAGNESIUM	0.5 PPM MAX
SODIUM	0.5 PPM MAX
POTASSIUM	0.5 PPM MAX
WATER QUALITY	DEMIN - ISO 3696 APPLICABLE

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

