

## **HEAVY DUTY EXTREME DIESEL ENGINE OILS API CK-4**

Specifically engineered to meet the latest requirements for EGR/EGP engines and the new federal regulations mandating reduced fuel consumption and lower emissions. For today's demanding engine requirements CK-4 oils must pass 2 new tests to evaluate oxidation stability and aeration control. API CK-4 15W40 meets or exceeds most OEM manufacturer's specifications and is backward compatible with CJ-4, Cl-4 PLUS, Cl-4 and CH-4. 10W30 meets and exceeds API CK-4 and is designed to maximize fuel economy in todays current engines and utilizes group II+ type baseoils.

10W30	15W40
0.0865	0.0869
81.7	113.9
12.2	15.6
145	145
237	226
-39	-33
6200	5500
1.00	1.00
9.1	9.5
	0.0865 81.7 12.2 145 237 -39 6200 1.00

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4







## PRODUCT SPECIFICATION data sheet

## **HEAVY DUTY EXTREME DIESEL ENGINE OILS API CK-4**

SAE GRADE 10W30 15W40

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

## APPLICATIONS MEETS OR EXCEEDS THE FOLLOWING API SERVICE AND OEM SPECIFICATIONS REQUIREMENTS:

• API: CK-4, CJ-4, CI-4PLUS, CI-4, CH-4

• CUMMINS: CES 20081, CES 20086, CES 20087

• DETROIT DIESEL: DFS 93K222, DFS 93K218, DFS

93K233

• RENAULT: RLD-4, RLD-3

• FORD: WSS-M2C171-F1

• CATERPILLAR: ECF-2, ECF-3

• DAIMLER: MB 228.31

• MTU: CATEGORY 2.1

• VOLVO: VDS 4.5, 4, 3

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



