

PREMIUM LOW ASH NATURAL GAS ENGINE OIL

This premium quality, low ash, and dispersant-detergent natural gas engine oil (NGEO) is formulated with superior Group II base stock and advanced additive systems. This provides exceptional deposit, wear, oxidation and nitration control as well as rust and corrosion protection. It is designed for use in four-stroke cycle engines fuelled by natural or liquified petroleum gas (LPG) to provide API CD service level performance and long catalyst life of emissions control system catalytic converters.

SAE GRADE	40
SPECIFIC GRAVITY, KG/L	N/A
VISCOSITY CST @ 40°C	128.9
VISCOSITY CST @ 100°C	13.4
VISCOSITY INDEX (D2270)	110
FLASH POINT (D92), °C	247
POUR POINT (D97), °C	-22
TBN	8.5
SULPHATED ASH, WT%	0.45

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS MEETS AND EXCEEDS THE REQUIREMENTS FOR:

- CATALYST MANUFACTURER'S LIMITS
- CATERPILLAR

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



PREMIUM LOW ASH NATURAL GAS ENGINE OIL

APPLICATIONS

MEETS AND EXCEEDS THE REQUIREMENTS FOR:

- COOPER INDUSTRIES - AJAX, COOPER, BESSEMER SUPERIOR
- FAIRBANKS MORSE
- DEUTZ - MWM
- MAN
- COMPATIBLE WITH NSCR - CATALYSTS TYPE EXHAUST
- DRESSER INDUSTRIES - CLARK, DRESSER RAND, WAUKESHA, WORTHINGTON
- BERGEN
- RUSHTON
- WARTSILA NSD

*NOTE: ALWAYS CONTACT THE TECHNICAL DEPARTMENT FOR NEGOTIATION RECOMMENDATIONS

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

