

PREMIUM MEDIUM ASH

Premium Medium Ash (PM 30/40) engine oils are formulated with superior Group II base stocks and the most advanced chemical additive systems. PM 30/40 provides exceptional wear and deposit control, outstanding oxidation and nitration stability, excellent TBN retention, and good dispersant-detergent balance in Turbo Charged natural gas engines. For use in four-stroke cycle engines fueled by LPG or natural gas. This oil meets and exceeds OEM requirements for API CD & CF

SAE GRADE	30	40
VISCOSITY CST @ 40°C	97.3	129.3
VISCOSITY CST @ 100°C	11.5	13.99
VISCOSITY INDEX	109	110
FLASH POINT, COC, °C	246	247
FIRE POINT, COC, °C	274	275
POUR POINT, °C	-24	-22
PHOSPHORUS, WT%	0.029	0.029
TBN (D2896)	8.5	8.5
TAN, (D664)	0.81	0.82
ZINC, WT%	0.032	0.032

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



PREMIUM MEDIUM ASH

SAE GRADE	30	40
SULPHATED ASH, WT%	0.89	0.89

APPLICATIONS

RECOMMENDED FOR MAJOR STATIONARY NATURAL GAS ENGINE BUILDERS:

- CATERPILLAR
- DRESSER INDUSTRIES - CLARK, DRESSER-RAND, WAUKESHA, WORTHINGTON
- DEUTZ - MWM
- MAN
- COMPATIBLE WITH NSCR-TYPE EXHAUST CATALYSTS
- COPPER INDUSTRIES - AJAX, BESSEMER SUPERIOR
- FAIRBANKS MORSE
- RUSHTON
- WARTSILA NSD

*NOTE: ALWAYS CONTACT THE TECHNICAL DEPARTMENT FOR NGENO RECOMMENDATIONS

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

