

SINGLE GRADE BXHD DIESEL ENGINE OIL

These oils are optimal for use in naturally aspirated, turbo charged or super charged diesel engines in passenger, pick up and delivery vehicles. Other ideal uses are for construction, farm and marine equipment requiring a single grade diesel engine oil. This formulation provides excellent varnish, sludge, carbon and oxidation control and protects against bearing and bushing corrosion.

SAE GRADE	10W	30W	40W	50W
DENSITY @ 15°C, KG/L	0.8794	0.8916	0.8922	0.8973
KINEMATIC VISCOSITY (D445) CST @ 40°C	42.5	93	156	208
KINEMATIC VISCOSITY (D445) CST @ 100°C	7.27	11.7	15.8	20.4
VISCOSITY INDEX (D2270)	110	110	102	136
FLASH POINT (D92), °C	210	227	228	210
POUR POINT (D97), °C	-37	-32	-24	-18
CCS VISCOSITY, CP @ -20°C	2910	N/A	N/A	N/A
SULPHATED ASH, MASS%	1	1	1	1
TBN	9	9	9	9
FOAM TEST	PASS	PASS	PASS	PASS

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SINGLE GRADE BXHD DIESEL ENGINE OIL

SAE GRADE

10W

30W

40W

50W

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

- EXCEEDS API SERVICE CLASSIFICATION CF, CF-2, GF-3
- RECOMMENDED FOR MOBILE HYDRAULIC EQUIPMENT SYSTEMS SPECIFYING ENGINE OIL
- RECOMMENDED FOR POWER SHIFT TRANSMISSIONS SPECIFYING ALLISON C-3, C-4 & CAT TO-2

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

