

SUPER MULTI-GRADE HYDRAULIC OILS

The Super Multi-Grade hydraulic oil is formulated with high quality base stocks and an advanced additive system to provide outstanding thermal and oxidation stability, excellent rust protection, anti-foam characteristics and demulsibility. This product is designed for hydraulic operations in all seasons.

KINEMATIC VISCOSITY CST @ 40°C	31.73
KINEMATIC VISCOSITY CST @ 100°C	7.43
VISCOSITY INDEX	213
FLASH POINT, °C	183
POUR POINT, °C	-54
BROOKFIELD VISCOSITY, @ -40°C	12.9
COLOR	LIGHT/PALE

APPLICATIONS

- DENSION HF-1, HF-2, HF-0
- SUNSTRAND
- EATON/VICKERS I-286-S, M-2950-S
- CINCINNATI MACHINE P-68, P-69, P-70

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SUPER MULTI-GRADE HYDRAULIC OILS

APPLICATIONS

- RACINE, VARIABLE VOLUME VANE PUMP
- REXROTH

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

