

SYNTHETIC DIESEL ENGINE OILS

A full synthetic oil utilizing Group III base stock oils and an advanced additive system to minimize combustion chamber ash deposits while allowing high alkaline reserves to protect engine components. The wide viscosity range allows superior low temperature fluidity, high oxidation and thermal stability to protect the engine against sludge and varnish deposits.

SAE GRADE	0W30	0W40	5W40	15W40
DENSITY @ 15.5°C, KG/L	0.846	0.866	0.877	0.881
KINEMATIC VISCOSITY (D445) CST @ 40°C	56.98	87.27	87.75	115
KINEMATIC VISCOSITY (D445) CST @ 100°C	10.26	15.14	14.76	15.05
VISCOSITY INDEX (D2270)	173	180	177	146
VISCOSITY CCS CP @ -25°C	N/A	N/A	N/A	5800
VISCOSITY CCS CP @ -35°C	5560	5360	5600	N/A
FLASH POINT (D92), °C	238	188	225	232
POUR POINT (D97), °C	-51	-54	-45	-43
TBN	10	10	10	10
ASH SULPHATE, MASS%	0.99	0.99	0.99	0.99
HT/HS, CP @ 150°C	3.09	3.55	3.85	4.27

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC DIESEL ENGINE OILS

SAE GRADE

0W30

0W40

5W40

15W40

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: CK-4: 0W40, 5W40 & 15W40, CJ-4, CI-4, CH-4
- MACK: ESO-4.5, E0-K/2, EO-L, EO-O PP 07', EO-N PP 03', EO-N PLUS, EO-M
- CATERPILLAR: IN/1K, ECF-3/1
- VOLVO: VDS-4.5/4/3/2
- MERCEDES BENZ: 228.31, 228.3
- MAN: M-3575, 3275
- ACE E7-04
- MIL-L-2104 E/F
- FORD: WSS-M2C171-F1
- API: SN: 5W40 & 15W40, SM, SL, SJ
- DETROIT DIESEL: 75E 270, 93K222/18/15/14
- EXTENTION SEQUENCE IN IIIIE, VE AND L-38 BENCH TEST
- CUMMINS: 20086, 20081, 20071, 20072, 20076, 20077, 20078
- RENAULT: RLD-4, 3
- GLOBAL DHD-1
- JASO DH-2
- ALLISON C-4/3

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

