

## SYNTHETIC GL-5 GEAR OIL

Specifically designed to meet the service requirements of API: GL-5, Eaton and Rockwell differentials. Formulated for superior flow ability to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

SAE GRADE	75W140	80W140
DENSITY @ 15.5°C, KG/L	0.8835	0.8835
KINEMATIC VISCOSITY (D445) CST @ 40°C	175.1	175.1
KINEMATIC VISCOSITY (D445) CST @ 100°C	24.85	24.85
VISCOSITY INDEX (D2270)	175	175
FLASH POINT (D92), °C	202	216
POUR POINT (D97), °C	-51	-51
BROOKFIELD VISCOSITY @-40°C	105000	105000

\*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-5
- MACK: GO-J, GO-H, GO-G

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## SYNTHETIC GL-5 GEAR OIL

### APPLICATIONS

#### MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- MT-1
- AIST/US STEEL 224
- SAE: J2360, MIL-2105E/F
- LIMITED SLIP
- NAVISTAR MPAPS B
- VOLVO 97035
- ROCKWELL: 076-E
- AGMA 9005-E02: 250.03, 250.04, 251.02, NO. 4
- CEC: L-45-A-99
- MACK TO-A PLUS
- MERITOR
- ZF FREEDOMLINE

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

