

SYNTHETIC GL-5 GEAR OIL (75W90)

Specifically designed to meet the service requirements of API: GL-5 , Eaton and Rockwell differentials. Formulated for superior flow ability to minimize gear wear, reduce frictional drag and protect against heavy loading failures in extreme weather conditions.

SAE GRADE	75W90
DENSITY @ 15.5°C, KG/L	0.8695
KINEMATIC VISCOSITY (D445) CST @ 40°C	109.3
KINEMATIC VISCOSITY (D445) CST @ 100°C	16.5
VISCOSITY INDEX (D2270)	159
FLASH POINT (D92), °C	204
POUR POINT (D97), °C	-51
BROOKFIELD VISCOSITY @-40°C	135000

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- API: GL-5
- AC DELCO 10-4051

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4



SYNTHETIC GL-5 GEAR OIL (75W90)

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- BMW 83222365987, 83229407768, 83229407803, 83229407804, 83229407808, 83229407870, 83229407871
- BMW OSP/SAF-XO/SAFX-LS
- BOT 328, 130M, 720
- CHRYSLER MS-8987/9763/9020
- CLARK MS8 REV.1
- DAF LKW (for long train intervals)
- FORD ES-PM M2013, WSD-M2C200-C, WSP- 197-A, WSP-M2C201-A, WSS-M2C939-A, FORD M2C119-A, 58- A, 197-A, FORD MC2108C, FORD 1045737, FORD 5021033 FOR FORD TRANSMISSION IB5, B5, MTX75, GM5,MT285/6, MMT6/6, MT75, R15M-D, R15MX-D, MT82, FORD XY-75W90-QLS, FORD XY 75W90-TQL, FORD XY-80W90-QL
- FUCHS TITAN RACE SYN-5
- GM 1050010, 1052271, 10950849, 10953455, 12345841, 12345977, 12378261, 12378557, 19352759, 88862624, 88862625, 88863089, 88863090, 88901362, 89021669, 89021671, 89021675, 89021676, 89021677, 92184900, 9985044, 9985290, 9985476, 9986115, 9986207, 9986290
- IVECO
- JOHN DEERE J11D
- KOMATSU/DRESSER B22-003-0005
- LAND ROVER TYK500010
- MAN 342 TYPE S1
- MACK GO-J
- MAZDA 0000-77-80W90-QT
- MB 235.0, 235.6, 235.7, 235.8, 235.11, 235.20, MB A 001989 17 03-10, A 001 989 27 03-10, A 001 989 28 03-10, A 001 989 58 03-10
- MIL-L 2105D/E
- MITSUBISHI 3775610, 8149630, MZ320345, DIAQUEEN LSD GEAR OIL
- NISSAN KLD 37-00001P
- –PORSCHE 000 043 205 30, 000 043 300 37, 000 043 305 04, Porsche SAF Carbon Mod, PORSCHE SAF-PD, SAF-XO, PORSCHE 958.341.536.00 (Full-Time Transfer Case with Torsen for Cayenne 92A/ 958 Diesel and S Hybrid from 2010 to 2018)
- RENAULT LKW
- SAE J2360
- SCANIA STO 1:0
- SUBARU SOA635001, 635048, SUBARU K0305Y0900, K0318Y0000, K0904AA080
- TOYOTA 08885-81006
- VOLVO 1161129-0, 31259380, VOLVO 97312, 97315
- VW/AUDI G 052 145 A2, 052 196, 052 539 A2, 052 911 A2
- ZF TE-ML 12B, 16F, 17B
- WHITE MOTORS MS 0016

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

