

TYPE F AUTOMATIC TRANSMISSION FLUID

Designed for automatic transmissions of some 1977 and earlier Ford automobiles and trucks where Type F is specified.

SAE GRADE	TYPE F
SPECIFIC GRAVITY @ 15.5°C	0.8493
KINEMATIC VISCOSITY (D445) CST @ 40°C	36.51
KINEMATIC VISCOSITY (D445) CST @ 100°C	7.82
VISCOSITY INDEX (D2270)	193
FLASH POINT (D92), °C	170
POUR POINT (D97), °C	-46

*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- FORD: M2C-33G & M2C-33F
- SAAB: 900 3-SPEED TRANSMISSION

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of its products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4





TYPE F AUTOMATIC TRANSMISSION FLUID

APPLICATIONS

MEETS OR EXCEEDS THE FOLLOWING SERVICE REQUIREMENTS:

- JAGUAR: 1990/1992 BURG-WARNER AUTOMATIC TRANSMISSION

In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4

