

## ZINC FREE HYDRAULIC OILS

Developed for use in high-speed, high-pressure piston, vane and gear pumps to meet the stringent requirements of severe hydraulic systems using high output and high pressure pumps. These oils are formulated from high quality base stock and specifically selected super-stabilized additives which exhibit oxidation, thermal stability and exceptional corrosion protection for copper-based alloys.

ISO GRADE	22	46
DENSITY @ 15°C	0.8519	0.8688
KINEMATIC VISCOSITY CST @ 40°C	19.68	46.37
KINEMATIC VISCOSITY CST @ 100°C	4.11	7.36
VISCOSITY INDEX	187	123
FLASH POINT, °C	158	182
POUR POINT, °C	-39	-30

### APPLICATIONS MEETS OR EXCEEDS REQUIREMENTS FOR:

- DIN 51524 PART 2
- DENISON: HF-O, HF-2

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*



## ZINC FREE HYDRAULIC OILS

### APPLICATIONS

#### MEETS OR EXCEEDS REQUIREMENTS FOR:

- VICKERS: I-286-S, M-2950-S
- CINCINNATIMILACRON: P68, P69, P70
- USS: 127, 136

\*NOTE: NOT APPROVED FOR USE IN JOHN DEERE OR HITACHI EQUIPMENT

*In order to continue to provide superior quality, BOSS LUBRICANTS reserves the right to change composition of it's products without notice. For the location of the Distributor nearest you, please call 1-800-844-9457. BOSS LUBRICANTS #112, 6303 30th Street S.E. Calgary, AB T2C 1R4*

